

View Online at <https://aerobasegroup.com/nsn/5930-00-465-4590>

Overall Length:

Between 1.210 inches and 1.220 inches

Overall Height:

0.638 inches

Body Diameter:

0.640 inches

Mounting Slot Width:

Between 0.133 inches and 0.147 inches

Body Height:

0.395 inches

Unthreaded Mounting Hole Diameter:

Between 0.133 inches and 0.147 inches

Distance Between Mounting Facility Centers:

Between 0.930 inches and 0.944 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and slot and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

115.00 actuation point degrees celsius and 125.00 actuation point degrees celsius and 95.00 deactuation point degrees celsius and 105.00 deactuation point degrees celsius and 20.00 differential point degrees celsius

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage and 400.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0