

View Online at <https://aerobasegroup.com/nsn/5930-00-465-7838>

Thread Class:

2a

Body Style:

Bushing mounted

Body Diameter:

0.870 inches

Bushing Length:

0.500 inches

Body Length:

0.780 inches

Actuator Diameter:

0.650 inches

Actuator Height:

0.250 inches

Actuator Color:

Red single actuator

Illuminated Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 2.000 amperes lamp dc and 4.000 amperes resistive ac and 2.000 amperes inductive ac and 2.000 amperes lamp ac

Test Data Document:

96906-ms27903 standard (includes industry or association standards, individual manufactureer standards, etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0