

View Online at <https://aerobasegroup.com/nsn/5930-00-465-9946>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Industrial use

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

2.013 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.190 inches

**Housing Length:**

2.460 inches

**Housing Width:**

1.000 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

1.000 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.750 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 9.0 ounces and 13.0 ounces

**Actuator Movement:**

Between 0.015 pretravel inches and 0.140 overtravel inches and 0.002 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0