

View Online at <https://aerobasegroup.com/nsn/5930-00-465-9946>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Industrial use

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.013 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.190 inches

Housing Length:

2.460 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.750 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 9.0 ounces and 13.0 ounces

Actuator Movement:

Between 0.015 pretravel inches and 0.140 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0