NSN 5930-00-466-1528

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-466-1528

Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
2.000 inches
Overall Height:
0.906 inches
Body Diameter:
1.062 inches
Mounting Slot Width:
0.172 inches
Body Height:
0.861 inches
Distance Between Mounting Facility Centers:
1.656 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating: Retwoon, 65.0 degrees fabrophoit and 350.0 degrees fabrophoit
Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit
Mounting Method: Bracket and slot
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
5.0 amperes resistive load first voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
110.00 actuation point degrees fahrenheit and 32.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
240.0 ac at sea level second voltage
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Disc w/flange

NSN 5930-00-466-1528

Thermostatic Switch - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0