## NSN 5930-00-466-1536

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-466-1536
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Moisture resistant and salt spray resistant and shock resistant and vibration resistant
Overall Length:
2.771 inches
Overall Height:
0.880 inches
Overall Width:
0.880 inches
Body Diameter:
0.520 inches
Bushing Length:
0.410 inches
Case Material:
Metal
Actuator Diameter:
0.375 inches
Actuator Height:
0.430 inches
Actuator Color:
Red single actuator
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
Check system close doors single actuator
Maximum Voltage Rating In Volts:
125.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
32
Thread Size:
0.562 inches
Nonpile-up Contact Arrangement:
1 two circuit, two positions momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 500.000 milliamperes inductive dc and 2.000 amperes resistive ac and 500.000 milliamperes inductive ac
Precious Material And Location:
Terminal surfaces and contacts and shorting bar silver

Un

**Thread Series Designator:** 

## NSN 5930-00-466-1536

Push Switch - Page 2 of 2



Terminal Type A	and Quantity	<b>/:</b>
-----------------	--------------	-----------

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0