

View Online at <https://aerobasegroup.com/nsn/5930-00-468-2528>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.125 inches

**Body Length:**

0.875 inches

**Body Width:**

0.531 inches

**Body Height:**

0.297 inches

**Actuator Length:**

0.281 inches

**Actuator Height:**

0.031 inches

**Actuator Width:**

0.234 inches

**Actuator Position-action Relationship:**

Left position maintained and right position maintained

**Actuator Position-locking Relationship:**

Left position locked in and right position locked in

**Actuator Color:**

Black single actuator

**Actuator Inscription:**

115 and 230 single actuator

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 6.000 amperes resistive ac

**Special Features:**

Actuator has screwdriver slot for actuation

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0