

View Online at <https://aerobasegroup.com/nsn/5930-00-468-2759>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Body Diameter:

Between 1.480 inches and 1.520 inches

Bushing Length:

Between 0.320 inches and 0.360 inches

Body Length:

Between 2.800 inches and 2.840 inches

Actuator Length:

Between 1.480 inches and 1.520 inches

Actuator Style:

Roller arm

Actuator Height:

Between 0.927 inches and 0.967 inches

Actuator Roller Diameter:

Between 0.730 inches and 0.770 inches

Actuator Roller Width:

Between 0.290 inches and 0.330 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 inch-ounces

Switch Actuating Force:

Between 192.0 inch-ounces and 400.0 inch-ounces

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc and 6.000 amperes motor dc

Test Data Document:

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0