

View Online at <https://aerobasegroup.com/nsn/5930-00-469-3407>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

3.055 inches

**Overall Height:**

1.313 inches

**Overall Width:**

1.281 inches

**First Flat Length:**

0.250 inches 2nd actuator

**Flat Height:**

0.218 inches 1st actuator

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

1.312 inches 2nd actuator

**Nonturn Device Radius:**

0.531 inches at 9: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 9: 00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

1 1st section rear

**Throw Quantity:**

3 1st section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device 2nd actuator

**Switch Actuator Indexing Position Quantity:**

3 1st actuator

**Shaft Type:**

Round, hollowed, flatted 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks 1st section front

**Switch Actuator Positioning Increment:**

30.0 degrees 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop all actuators

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Special Features:**

2nd shaft accommodates variable resistor

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0