

View Online at <https://aerobasegroup.com/nsn/5930-00-469-8181>

Thread Class:

3a single pressure connection

Overall Length:

3.500 inches

Overall Diameter:

1.250 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.688 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Plug-in terminal

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

450.00 pounds per square inch

Thread Size:

0.4375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Sensing Element Burst Pressure:

600.00 pounds per square inch

Terminal Type:

Wire lead

Contact Load Current Rating:

2.0 amperes inductive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

350.00 actuation point pounds per square inch gage and 400.00 deactuation point pounds per square inch gage and 50.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Pressure Connector Type:

Swivel nut, gasket seal, threaded internal single connection

Frequency In Hertz:

400.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0