

View Online at <https://aerobasegroup.com/nsn/5930-00-469-9429>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.373 inches and 0.377 inches

Body Length:

Between 0.866 inches and 0.886 inches

Body Width:

Between 0.336 inches and 0.356 inches

Body Height:

Between 0.347 inches and 0.367 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

0.078 inches

Actuator Height:

0.145 inches

Actuator Free Position Height:

0.425 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 5.0 ounces and 17.0 ounces

Actuator Movement:

0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0