

View Online at <https://aerobasegroup.com/nsn/5930-00-470-0327>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.594 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Diameter:

0.416 inches

Bushing Length:

0.500 inches

Actuator Diameter:

0.875 inches

Actuator Height:

0.250 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc and 25.000 milliamperes lamp dc and 1.000 amperes resistive ac and 0.500 amperes inductive ac and 25.000 milliamperes lamp ac

Test Data Document:

81349-mil-s-6743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

96906-ms17975 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0