

View Online at <https://aerobasegroup.com/nsn/5930-00-470-0327>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

1.594 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**Body Diameter:**

0.416 inches

**Bushing Length:**

0.500 inches

**Actuator Diameter:**

0.875 inches

**Actuator Height:**

0.250 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc and 25.000 milliamperes lamp dc and 1.000 amperes resistive ac and 0.500 amperes inductive ac and 25.000 milliamperes lamp ac

**Test Data Document:**

81349-mil-s-6743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 tab, solder lug

**Specification Data:**

96906-ms17975 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0