

View Online at <https://aerobasegroup.com/nsn/5930-00-470-1449>

**Thread Class:**

2a all threaded stud

**Thread Length:**

0.375 inches all threaded stud

**Overall Height:**

Between 0.795 inches and 0.850 inches

**Body Height:**

Between 0.350 inches and 0.405 inches

**Overall Diameter:**

0.640 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -60.0 degrees fahrenheit and 400.0 degrees fahrenheit

**Mounting Method:**

Threaded stud

**Features Provided:**

Hermetically sealed case

**Thready Qty Per Inch (tpi):**

32 all threaded stud

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.138 inches all threaded stud

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 500.0 milliamperes lamp load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

255.00 actuation point degrees fahrenheit and 225.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc

**Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc all threaded stud

**Specification Data:**

81349-mil-s-24236/24 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0