

View Online at <https://aerobasegroup.com/nsn/5930-00-471-2003>

Body Style:

Bushing mounted

Body Diameter:

Between 0.552 inches and 0.572 inches

Bushing Length:

Between 0.422 inches and 0.454 inches

Body Length:

Between 0.500 inches and 0.562 inches

Actuator Diameter:

Between 0.355 inches and 0.395 inches

Actuator Height:

Between 0.235 inches and 0.265 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, double break, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0