# NSN 5930-00-471-2690

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-471-2690

# Body Style:

Hole mounted

## Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

# Body Length:

0.781 inches

## **Body Width:**

0.250 inches

# Body Height:

0.761 inches

#### **Unthreaded Mounting Hole Diameter:**

0.088 inches

#### Actuator Length:

0.125 inches

#### Actuator Style:

Rectangular

# Actuator Height:

0.150 inches

#### Actuator Width:

0.125 inches

# Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

# Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

## Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

#### Switch Release Force:

4.0 ounces

#### Switch Actuating Force:

16.0 ounces

#### **Actuator Movement:**

Between 0.060 pretravel inches and 0.012 overtravel inches and 0.035 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac

# **Terminal Type And Quantity:**

8 tab, solder lug

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5930-00-471-2690

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

