

View Online at <https://aerobasegroup.com/nsn/5930-00-471-2871>

Thread Class:

2a all threaded stud

Thread Length:

0.255 inches all threaded stud

Hazardous Locations/environmental Protection:

Gastight

Overall Height:

0.923 inches

Body Height:

0.290 inches

Overall Diameter:

0.605 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

6.0 amperes resistive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

216.00 actuation point degrees fahrenheit and 200.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Frequency In Hertz:

4000.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0