## NSN 5930-00-471-4573

Thermostatic Switch - Page 1 of 2

230.0 ac at sea level first voltage



View Online at https://aerobasegroup.com/nsn/5930-00-471-4573

Overall Length:
Overall Length: 3.312 inches
Overall Height:
5.375 inches
Overall Width:
2.500 inches
Mounting Slot Width:
0.375 inches
Body Length:
2.312 inches
Capillary Tube Length:
96.0 inches
Bulb Length:
7.250 inches
Bulb Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
1.500 inches
Longest Vertical Distance Between Mounting Centers:
3.625 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Slot
Contact Action Stimulus:
Decrease
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
6.5 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+20.00/+75.00 actuation point degrees fahrenheit and +17.00/+72.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point knob with scale and external actuation point knob with scale
Contact Voltage Rating In Volts:

## NSN 5930-00-471-4573

Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A048b0