

View Online at <https://aerobasegroup.com/nsn/5930-00-471-6319>

Thread Class:

2a single mounting facility

Thread Length:

0.370 inches single mounting facility and 0.380 inches single mounting facility

Overall Length:

Between 2.823 inches and 2.947 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

1.250 inches 2nd actuator

Overall Diameter:

1.250 inches

Nonturn Device Radius:

0.521 inches at 3: 00 o'clock and 0.541 inches at 3: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 2nd actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 2nd section rear

Switch Actuator Positioning Increment:

60.0 degrees 2nd actuator

Detent Rotational Torque Range:

+15.000/+30.000 inch-ounces all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0