

View Online at <https://aerobasegroup.com/nsn/5930-00-471-6339>

Thread Class:

2a single mounting facility

Thread Length:

0.255 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.976 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

1.003 inches single actuator

Overall Diameter:

Between 0.473 inches and 0.551 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

10 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+8.000/+24.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Stationary contact surfaces gold and moving contacts silver and terminal surfaces silver

Precious Material:

Gold and silver

Style Designator:

Snap or line

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0