

View Online at <https://aerobasegroup.com/nsn/5930-00-472-1931>

**Thread Class:**

2b single mounting facility

**Overall Length:**

2.625 inches

**Overall Height:**

2.500 inches

**First Flat Length:**

0.875 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.187 inches single actuator

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

04009

**Knob Manufacturer Part Number:**

80156-733

**Knob Specification Markings:**

Arrow symbol

**Longest Horizontal Distance Between Mounting Centers:**

1.641 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.641 inches single mounting facility

**Operating Temperature Range:**

+0.0/+50.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

3 single section rear

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 highest ac voltage rating at sea level

**Rotor Through Connection Quantity:**

1 single section

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, parallel flatted, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level

**Special Features:**

Fungus treated

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0