

View Online at <https://aerobasegroup.com/nsn/5930-00-472-2014>

Thread Class:

2b single mounting facility

First Flat Length:

0.203 inches single actuator

Flat Height:

0.126 inches single actuator

Shaft Diameter:

0.156 inches single actuator

Shaft Length:

0.719 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.688 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

3 single section front

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

48 single mounting facility

Thread Size:

0.099 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

3.0 amperes resistive load dc at sea level

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0