

View Online at <https://aerobasegroup.com/nsn/5930-00-472-4422>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Submersible

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.860 inches

Body Width:

0.335 inches

Body Height:

0.988 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

Between 0.088 inches and 0.090 inches

Actuator Length:

0.531 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.785 inches

Actuator Roller Diameter:

0.188 inches

Actuator Roller Width:

0.125 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

5.0 ounces

Switch Actuating Force:

16.0 ounces

Actuator Movement:

Between 0.120 pretravel inches and 0.025 overtravel inches and 0.058 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0