

View Online at <https://aerobasegroup.com/nsn/5930-00-472-4422>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Submersible

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.860 inches

**Body Width:**

0.335 inches

**Body Height:**

0.988 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

Between 0.088 inches and 0.090 inches

**Actuator Length:**

0.531 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.785 inches

**Actuator Roller Diameter:**

0.188 inches

**Actuator Roller Width:**

0.125 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

5.0 ounces

**Switch Actuating Force:**

16.0 ounces

**Actuator Movement:**

Between 0.120 pretravel inches and 0.025 overtravel inches and 0.058 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 5.000 amperes resistive ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0