# NSN 5930-00-472-7866

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-472-7866

# **Thread Class:**

2a single mounting facility

### Thread Length:

0.250 inches single mounting facility

# **Overall Length:**

2.426 inches

#### **Overall Height:**

1.031 inches

#### **Overall Width:**

0.938 inches

#### Shaft Diameter:

0.125 inches single actuator

# Shaft Length:

1.250 inches single actuator

#### **Nonturn Device Radius:**

# 0.438 inches at 9:00 o'clock

# Individual Section Quantity:

2

#### Knob Manufacturer Code:

71590

# Knob Manufacturer Part Number:

P106

#### Nonturn Device Type:

Tab at 9: 00 o'clock

#### **Operating Tempurature Range:**

-65.0/+175.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### **Throw Quantity:**

11 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Features Provided:**

Actuator knob

#### **Thread Size:**

0.250 inches single mounting facility

# **Contact Voltage Rating In Volts:**

6.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

11 single actuator

# **NSN 5930-00-472-7866** Rotary Switch - Page 2 of 2

Shaft Type:
Round single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
0.5 amperes resistive load dc at sea level
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A052b0

