

View Online at <https://aerobasegroup.com/nsn/5930-00-473-3386>

Body Style:

Bushing mounted

Body Diameter:

Between 0.372 inches and 0.378 inches

Bushing Length:

Between 0.247 inches and 0.253 inches

Actuator Diameter:

Between 0.130 inches and 0.170 inches

Actuator Height:

Between 0.140 inches and 0.180 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 250.000 milliamperes inductive dc and 250.000 milliamperes lamp dc and 1.000 amperes resistive ac and 250.000 milliamperes inductive ac and 250.000 milliamperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0