## NSN 5930-00-473-3443

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-473-3443

#### **Thread Length:**

0.370 inches single mounting facility and 0.380 inches single mounting facility

#### **Overall Length:**

2.249 inches

#### First Flat Length:

0.437 inches single actuator

#### Flat Height:

0.217 inches single actuator and 0.221 inches single actuator

#### **Shaft Diameter:**

0.247 inches single actuator and 0.250 inches single actuator

#### **Shaft Length:**

0.875 inches single actuator

#### **Overall Diameter:**

Between 1.235 inches and 1.265 inches

#### **Nonturn Device Radius:**

0.503 inches at 3: 00 o'clock and 0.523 inches at 3: 00 o'clock

#### **Individual Section Quantity:**

1

#### **Nonturn Device Type:**

Tab at 3: 00 o'clock

## **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

#### **Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## **Shaft Flat/slot Angular Location:**

165.0 degrees from contact position 1 single actuator

## **Switch Actuator Indexing Position Quantity:**

3 single actuator

#### **Shaft Type:**

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

#### **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

#### **Switch Actuator Stop Device Type:**

Fixed stop single actuator

# NSN 5930-00-473-3443

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

1.0 amperes resistive load ac at sea level

**Style Designator:** 

Circular wafer, bushing mount

#### **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0