

View Online at <https://aerobasegroup.com/nsn/5930-00-475-5537>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.938 inches

Body Width:

0.688 inches

Body Height:

0.969 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.190 inches

Actuator Height:

5.446 inches

End Application:

P-22 fire truck, generator set, diesel engine, 100kw, pu-495, truck, fire/crash p-10, assault amphibious vehicle, command (aavc-7a1), armored vehicle launch bridge (m60a1 & m48a5), truck, fire/crash p12, bridge armor vehicle (avlb) - model m60a1, truck, fire/crash p8, vehicle, recovery m-578; artic kit for hemtt family (heavy expanded mobility tactical trucks)

Inclosure Type:

Fully enclosed

Mounting Method:

Slot and unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, both positions maintained single switch unit

Criticality Code Justification:

Feat

Special Features:

Failure of this part can result in a non-mission capable vehicle or personnel injury. Weapon system essential

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0