NSN 5930-00-476-4521

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-476-4521

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.940 inches

Overall Height:

3.190 inches

Overall Width:

2.280 inches

Actuator Style:

Round

Actuator Diameter:

0.490 inches

Actuator Height:

0.500 inches

Housing Height:

3.190 inches

Housing Length:

4.940 inches

Housing Width:

2.280 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.437 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.812 inches

Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

20

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

160.0 inch-ounces

Switch Actuating Force:

224.0 inch-ounces

NSN 5930-00-476-4521

Sensitive Switch - Page 2 of 2



Actuator Movement:

18.0 pretravel degrees and 14.0 overtravel degrees and 3.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

750.000 milliamperes resistive dc and 2.500 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0