NSN 5930-00-476-4521

Sensitive Switch - Page 1 of 2

224.0 inch-ounces



View Online at https://aerobasegroup.com/nsn/5930-00-476-4521

| Padu Stula |
|--|
| Body Style: Hole mounted |
| Hazardous Locations/environmental Protection: |
| |
| Dustproof Overall Length: |
| Overall Length: |
| 4.940 inches |
| Overall Height: |
| 3.190 inches |
| Overall Width: |
| 2.280 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.490 inches |
| Actuator Height: |
| 0.500 inches |
| Housing Height: |
| 3.190 inches |
| Housing Length: |
| 4.940 inches |
| Housing Width: |
| 2.280 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 2.437 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width: |
| 1.812 inches |
| Maximum Voltage Rating In Volts: |
| 600.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded hole |
| Thready Qty Per Inch (tpi): |
| 20 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 1 two circuit, double break/double make, one position momentary single switch unit |
| Switch Release Force: |
| 160.0 inch-ounces |
| Switch Actuating Force: |

NSN 5930-00-476-4521

Sensitive Switch - Page 2 of 2



| Δ | ctu | ato | - М | ΛV/ | am. | ۵ni | ŀ |
|---|-----|-----|-----|-----|------|-----|----|
| н | CLU | alu | IVI | OVE | 2111 | | L. |

18.0 pretravel degrees and 14.0 overtravel degrees and 3.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

750.000 milliamperes resistive dc and 2.500 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0