## NSN 5930-00-476-4802

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-476-4802

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Weatherproof
Body Diameter:
0.782 inches
Bushing Length:
0.340 inches
Body Length:
1.100 inches
Actuator Length:
2.000 inches
Actuator Style:
Adjustable arm
Actuator Diameter:
0.180 inches
Actuator Height:
1.240 inches
Actuator Width:
1.600 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
F-4 phantom, f-15 aircraft.
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
24.0 ounces

Actuator Movement:

60.0 pretravel degrees and 292.0 overtravel degrees and 4.0 differential degrees

## NSN 5930-00-476-4802

Sensitive Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 3.300 amperes motor ac

Special Features:	
Weapon system essential	
Thread Series Designator:	
Uns	

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0