NSN 5930-00-476-6321

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-476-6321 **Thread Class:** 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Hazardous Locations/environmental Protection:** Moisture proof **Overall Length:** 2.312 inches **Overall Height:** 1.310 inches **Overall Width:** 1.250 inches First Flat Length: 0.380 inches single actuator Flat Height: 0.219 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.500 inches single actuator **Nonturn Device Radius:** 0.530 inches at 3: 00 o'clock **Individual Section Quantity: Nonturn Device Type:** Tab at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Shaft Flat/slot Angular Location:** 180.0 degrees from contact position 1 single actuator **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round, flatted single actuator

Terminal Type: Tab, solder lug

NSN 5930-00-476-6321 Rotary Switch - Page 2 of 2



Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Detent Rotational Torque Range:
+1.000/+6.000 inch-pounds single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
1.0 amperes resistive load ac at sea level
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A052b0