NSN 5930-00-477-0080

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-477-0080

Thread Length:
0.275 inches single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
0.665 inches
Overall Diameter:
0.500 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-55.0/+7.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section rear
Throw Quantity:
2 single section rear
Mounting Method:
Threaded bushing single mounting facility
Features Provided:
Metallic inclosure
Contact Voltage Rating In Volts:
28.0 dc at sea level
Switch Actuator Indexing Position Quantity:
Switch Actuator Indexing Position Quantity: 2 single actuator
2 single actuator
2 single actuator Contact Switching Action:
2 single actuator Contact Switching Action: Breaks before makes single section rear
2 single actuator Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment:
2 single actuator Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 36.0 degrees single actuator
2 single actuator Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 36.0 degrees single actuator Switch Actuator Stop Device Type:
2 single actuator Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 36.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator
2 single actuator Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 36.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating:
2 single actuator Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 36.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 250.0 milliamperes resistive load dc at sea level
2 single actuator Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 36.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 250.0 milliamperes resistive load dc at sea level Style Designator:
2 single actuator Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 36.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 250.0 milliamperes resistive load dc at sea level Style Designator: Miniature, bushing mount
2 single actuator Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 36.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 250.0 milliamperes resistive load dc at sea level Style Designator: Miniature, bushing mount Shelf Life:
2 single actuator Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 36.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 250.0 milliamperes resistive load dc at sea level Style Designator: Miniature, bushing mount Shelf Life: N/a

No

NSN 5930-00-477-0080Rotary Switch - Page 2 of 2



Fiig:

A052b0