

View Online at <https://aerobasegroup.com/nsn/5930-00-477-2360>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.562 inches

Overall Height:

2.224 inches

Overall Width:

0.546 inches

Bushing Length:

0.468 inches

Body Length:

0.562 inches

Body Width:

0.546 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

1.050 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked in and out and center position no locking action

Maximum Voltage Rating In Volts:

125.0 ac and 50.0 dc

Mounting Surface To Terminal End Distance:

0.706 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A053a0