

View Online at <https://aerobasegroup.com/nsn/5930-00-477-8748>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Driptight and shock resistant and vibration resistant

**Overall Length:**

1.950 inches

**Overall Height:**

0.668 inches

**Overall Width:**

0.668 inches

**Body Diameter:**

0.668 inches

**Bushing Length:**

0.410 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.468 inches

**Actuator Height:**

0.560 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.562 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 0.500 amperes inductive ac

**Precious Material And Location:**

Shorting bar surfaces and contacts gold and shorting bar silver

**Unable To Decode:**

Unable to decode and unable to decode

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0