

View Online at <https://aerobasegroup.com/nsn/5930-00-477-8748>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Driptight and shock resistant and vibration resistant

Overall Length:

1.950 inches

Overall Height:

0.668 inches

Overall Width:

0.668 inches

Body Diameter:

0.668 inches

Bushing Length:

0.410 inches

Case Material:

Metal

Actuator Diameter:

0.468 inches

Actuator Height:

0.560 inches

Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.562 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 0.500 amperes inductive ac

Precious Material And Location:

Shorting bar surfaces and contacts gold and shorting bar silver

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Un

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0