

View Online at <https://aerobasegroup.com/nsn/5930-00-477-9157>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.310 inches single mounting facility

**Overall Length:**

3.685 inches

**First Flat Length:**

0.310 inches 2nd actuator

**Flat Height:**

0.090 inches 1st actuator

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

1.375 inches 2nd actuator

**Overall Diameter:**

1.875 inches

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Flatted bushing at 9: 00 o'clock

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

14 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Variable resistor

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from contact position 1 1st actuator

**Switch Actuator Indexing Position Quantity:**

14 1st actuator

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

20.0 degrees 1st actuator

**Detent Rotational Torque Range:**

+20.000/+75.000 inch-ounces 1st actuator

**Switch Actuator Stop Device Type:**

Adjustable stop 1st actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Special Features:**

Three dummy lugs rear ea section, outer shaft also flatted

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0