

View Online at <https://aerobasegroup.com/nsn/5930-00-477-9157>

Thread Class:

2a single mounting facility

Thread Length:

0.310 inches single mounting facility

Overall Length:

3.685 inches

First Flat Length:

0.310 inches 2nd actuator

Flat Height:

0.090 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

1.375 inches 2nd actuator

Overall Diameter:

1.875 inches

Individual Section Quantity:

2

Nonturn Device Type:

Flatted bushing at 9: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

14 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 1st actuator

Switch Actuator Indexing Position Quantity:

14 1st actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

20.0 degrees 1st actuator

Detent Rotational Torque Range:

+20.000/+75.000 inch-ounces 1st actuator

Switch Actuator Stop Device Type:

Adjustable stop 1st actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Special Features:

Three dummy lugs rear ea section, outer shaft also flatted

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0