# NSN 5930-00-477-9288

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-477-9288

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

2.352 inches

#### **Overall Height:**

1.000 inches

#### **Overall Width:**

0.969 inches

#### Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

# Shaft Length:

1.375 inches single actuator

#### **Nonturn Device Radius:**

# 0.375 inches at 3: 00 o'clock

### Individual Section Quantity:

2

#### Nonturn Device Type:

Tab at 3: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

#### **Throw Quantity:**

12 each section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.375 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

### **Rotor Through Connection Quantity:**

1 each section

### Switch Actuator Indexing Position Quantity:

12 single actuator

### Shaft Type:

Round single actuator

# **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-00-477-9288

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Adjustable stop single actuator

# **Contact Load Current Rating:**

550.0 milliamperes resistive load dc at sea level

# Style Designator:

Circular wafer, bushing mount

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0