

View Online at <https://aerobasegroup.com/nsn/5930-00-478-2486>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

7.938 inches

**Overall Height:**

2.910 inches

**Overall Width:**

2.810 inches

**Individual Section Quantity:**

6

**Knob Manufacturer Code:**

82121

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.188 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load lowest ac voltage rating at sea level

**Precious Material And Location:**

Contact and rotor blade surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0