

View Online at <https://aerobasegroup.com/nsn/5930-00-478-3079>

Thread Class:

2a single mounting facility

Thread Length:

0.340 inches single mounting facility

Overall Length:

3.450 inches

Overall Height:

1.120 inches

Overall Width:

0.910 inches

First Flat Length:

0.340 inches single actuator

Flat Height:

0.093 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.570 inches single actuator

Nonturn Device Radius:

0.250 inches at 6:00 o'clock

Individual Section Quantity:

7

Nonturn Device Type:

Pin at 6:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Cam actuated

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, one position momentary each switch each section periphery

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 3.0 amperes inductive load dc at sea level and 2.4 amperes lamp load dc at sea level and 4.0 amperes motor load dc at sea level

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0