## NSN 5930-00-478-4889

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-478-4889

view Online at https://aerobasegroup.com/nish/0000-00-470-4000
Body Style:
Panel mount
Overall Length:
1.200 inches
Overall Height:
2.968 inches
Overall Width:
0.960 inches
Body Length:
0.844 inches
Body Width:
0.960 inches
Case Material:
Metal
Actuator Length:
1.040 inches
Actuator Style:
Rectangular
Actuator Height:
0.140 inches
Actuator Width:
0.800 inches
Maximum Voltage Rating In Volts:
115.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac
Special Features:
Horizontally split lens
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

5 tab, solder lug and 6 turret

## **Specification Data:**

81349-mil-s-22885/9 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5930-00-478-4889

Push Switch - Page 2 of 2



Demi			

No

Fiig:

A053a0