# NSN 5930-00-478-7334

Rotary Switch Section - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-478-7334

## **Overall Diameter:**

Between 1.833 inches and 1.853 inches

#### Body Thickness:

0.062 inches

### **Unthreaded Mounting Hole Diameter:**

0.147 inches single mounting facility

## Distance Between Mounting Facility Centers:

1.557 inches single mounting facility and 1.567 inches single mounting facility

## **Operating Tempurature Range:**

-54.0/+95.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 single section rear

Throw Quantity:

20 single section front

## Mounting Method:

Strut single mounting facility and unthreaded hole single mounting facility

## Contact Voltage Rating In Volts:

28.0 dc at sea level

## Rotor Through Connection Quantity:

1 single section

## Mounting Facility Pattern:

Two position in-line single mounting facility

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Makes before breaks single section rear

## **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

## Precious Material And Location:

Clips and rotor blades silver and clip surfaces and rotor blade surfaces gold

#### **Precious Material:**

Silver and gold

## Style Designator:

Switch section, rotary

Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5930-00-478-7334

Rotary Switch Section - Page 2 of 2

**Fiig:** A052b0

