

View Online at <https://aerobasegroup.com/nsn/5930-00-478-9165>

Thread Length:

0.359 inches single mounting facility and 0.391 inches single mounting facility

Overall Length:

2.454 inches

First Flat Length:

0.296 inches single actuator and 0.328 inches single actuator

Flat Height:

0.211 inches single actuator and 0.221 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.750 inches single actuator

Nonturn Device Radius:

0.515 inches at 3: 00 o'clock and 0.547 inches at 3: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

11 each section rear

Mounting Method:

Threaded bushing single mounting facility

Shaft Flat/slot Angular Location:

150.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

11 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Style Designator:

Circular wafer, bushing mount

Reference Number Differentiating Characteristics:

Mil-q-21549b-sp24-1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0

Mil-std (military Standard):

Mil-q-21549 spec.