

View Online at <https://aerobasegroup.com/nsn/5930-00-479-7633>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Length:

1.597 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

1.062 inches 2nd actuator

Overall Diameter:

1.310 inches

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 9:00 o'clock

Operating Temperature Range:

-20.0/+110.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section front

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 1st actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees 1st actuator

Detent Rotational Torque Range:

+20.000/+48.000 inch-ounces 1st actuator

Switch Actuator Stop Device Type:

Adjustable stop 1st actuator

Contact Load Current Rating:

750.0 milliamperes resistive load ac at sea level

Special Features:

Second actuator actuates resistor variable

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0