

View Online at <https://aerobasegroup.com/nsn/5930-00-479-7635>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

1.597 inches

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

1.062 inches 2nd actuator

**Overall Diameter:**

1.310 inches

**Nonturn Device Radius:**

0.531 inches at 3: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 9: 00 o'clock

**Operating Temperature Range:**

-20.0/+110.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section front

**Throw Quantity:**

3 single section front

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Variable resistor

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

3 1st actuator

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section front

**Switch Actuator Positioning Increment:**

30.0 degrees 1st actuator

**Detent Rotational Torque Range:**

+20.000/+48.000 inch-ounces 1st actuator

**Switch Actuator Stop Device Type:**

Adjustable stop 1st actuator

**Contact Load Current Rating:**

750.0 milliamperes resistive load ac at sea level

**Special Features:**

Second shaft actuates resistor variable

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0