NSN 5930-00-480-2046

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-480-2046

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.242 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Wire lead

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

NSN 5930-00-480-2046

Rotary Switch - Page 2 of 2



| Switch Actuator Stop Device Type: |
|---|
| Adjustable stop single actuator |
| Contact Load Current Rating: |
| 200.0 milliamperes resistive load dc at sea level |
| Precious Material And Location: |
| Rotor contact surface rhodium |
| Precious Material: |
| Rhodium |
| Style Designator: |
| Miniature, bushing mount |
| Thread Series Designator: |
| Unf single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A052b0