

View Online at <https://aerobasegroup.com/nsn/5930-00-480-9407>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Bushing Length:**

0.470 inches

**Body Length:**

1.437 inches

**Body Width:**

1.340 inches

**Body Height:**

1.000 inches

**Actuator Style:**

Round, threaded

**Actuator Height:**

0.600 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary, two positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 11.000 amperes resistive ac and 8.000 amperes inductive ac and 2.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0