

View Online at <https://aerobasegroup.com/nsn/5930-00-481-7542>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.188 inches

**Body Length:**

0.616 inches

**Body Width:**

0.316 inches

**Body Height:**

0.600 inches

**Unthreaded Mounting Hole Diameter:**

0.091 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.060 inches

**Actuator Height:**

0.095 inches

**Actuator Free Position Height:**

0.145 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0