

View Online at <https://aerobasegroup.com/nsn/5930-00-482-0341>

Thread Class:

2a single mounting facility

Thread Length:

0.427 inches single mounting facility and 0.447 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

Between 2.462 inches and 2.522 inches

First Flat Length:

0.240 inches single actuator and 0.260 inches single actuator

Flat Height:

0.205 inches single actuator and 0.215 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.255 inches single actuator

Shaft Length:

0.792 inches single actuator and 0.832 inches single actuator

Overall Diameter:

Between 1.026 inches and 1.046 inches

Nonturn Device Radius:

0.422 inches at 3:00 o'clock and 0.442 inches at 3:00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0